

STANDARD AFM® / SAND FILTERS

HFS SERIES Ø 415-960



Ref	ID	Ø D	H	O	A	B	I/O	Filt. Surface	AFM® G3 / G2 / G1 (21 Kg) Sand(2-3/0.7-1.2/0.4-0.8)(25 Kg)
112041	HFS-6	415	861	190	260	190	2"	0,13 m ²	0 / 1 / 2
112046	HFS-8	460	861	190	260	190	2"	0,16 m ²	0 / 1 / 3
112052	HFS-10	520	931	190	310	190	2"	0,20 m ²	0 / 2 / 4
112064	HFS-15	640	1090	305*	310	190	2"	0,30 m ²	0 / 4 / 8
112072	HFS-20	720	1140	305*	360	190	2"	0,40 m ²	0 / 4 / 12
112084	HFS-30	840	1190	355*	360	190	2"	0,52 m ²	4 / 4 / 16
112096	HFS-35	960	1240	355*	360	250	2 ½"	0,70 m ²	5 / 5 / 24

HFS SERIES 500 - 600 BED HEIGHT

Dimensions in mm.

Design pressure 2,5 Kg/cm² | Test pressure 3,75 Kg/cm².

Big transparent top lid.*

Internal steel reinforced filter.


Special diffuser for Sand / AFM®.

Female threads (GAS) in GRP are part of the body.

Large diameter internal piping designed for both Sand / AFM® requirements.

Laterals designed for proper filtration and backwash.

MANOMETER KIT INCLUDED



Threaded connections
integrated in body

Big transparent top lid

Top diffuser

Laterals

Drain plug

